

SNP SERIES(+85℃, nonpolar無極性)

◆ DIMENSIONS

Voltage	6.3V		10V		16V		25V	
Cap(μF)	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
0.47								
1								
2.2								
3.3								
4.7							5*11	26
10					5*11	42	5*11	42
22			5*11	57	5*11	57	6.3*11	65
33	5*11	64	5*11	64	5*11	70	6.3*11	80
47	5*11	76	5*11	76	6.3*11	95	6.3*11	95
100	6.3*11	125	6.3*11	125	8*12	160	8*12	160
220	8*12	215	8*12	215	10*12.5	275	10*16	305
330	8*12	265	10*16	345	10*16	375	12.5*20	450
470	10*12	370	10*16	410	10*20	485	12.5*20	540
1000	10*20	650	10*20	620	12.5*25	855	16*25	950
			12.5*20	720				
2200	12.5*25	1160	16*25	1280	16*30	1510	18*35	1620
3300	16*25	1570	16*30	1690	18*35	1980		
4700	16*30	2020	18*35	2160				
6800	18*35	2600						

Maximum Allowable Ripple Current (mA rms) at 85℃ 120Hz

Case Size ΦD X L (mm)

Voltage	35V		50V		63V		100V	
Cap(μF)	Size	Ripple	Size	Ripple	Size	Ripple	Size	Ripple
0.47			5*11	11			5*11	14
0.68			5*11	13				
1			5*11	17	5*11	18	5*11	21
1.5			5*11	20				
2.2			5*11	25			6.3*11	34
3.3			5*11	27	5*11	28	6.3*11	39
4.7	5*11	34	5*11	34	6.3*11	34	6.3*11	47
10	5*11	43	6.3*11	52	6.3*11	57	8*12	71
22	6.3*11	73	8*12	89	8*12	95	10*16	135
33	8*12	100	8*12	105	10*12.5	135	12.5*20	220
47	8*12	120	8*12	130	10*16	180	12.5*20	240
			10*12.5	150				
68			10*16	198				
100	10*12.5	187	10*20	265	12.5*20	320	16*25	425
	10*16	230						
220	12.5*20	410	12.5*25	480	16*25	574	18*35	720
330	12.5*20	505	16*25	650	16*30	655		
470	12.5*25	655	16*30	835	18*35	965		
1000	16*30	1140						
2200			22*40	1800				

Maximum Allowable Ripple Current (mA rms) at 85℃ 120Hz

Case Size ΦD X L (mm)